

YK710XE-10

Standard type: Large type

● LOW COST HIGH PERFORMANCE MODEL



- Arm length 710mm
- Maximum payload 10kg

Ordering method

YK710XE-10-200

RCX340-4

Model	Maximum payload	Z axis stroke	Tool flange	Hollow shaft	Cable	Controller / Number of controllable axes	Safety standard	Option A (OP.A)	Option B (OP.B)	Option C (OP.C)	Option D (OP.D)	Option E (OP.E)	Absolute battery
			No entry: None F: With tool flange	No entry: None S: With hollow shaft	3L: 3.5m 5L: 5m 10L: 10m								

Specify various controller setting items. RCX340 ▶ **P.566**

Note. The return-to-origin method is provided only in the sensor specifications, but not in the stroke end specifications.

Specifications

		X-axis	Y-axis	Z-axis	R-axis
Axis specifications	Arm length	435 mm	275 mm	200 mm	-
	Rotation angle	+/-134 °	+/-152 °	-	+/-360 °
AC servo motor output		400 W	200 W	200 W	200 W
Deceleration mechanism	Transmission method	Direct-coupled		Timing belt	
	Speed reducer to output	Direct-coupled		Timing belt	
Repeatability ^{Note 1}		+/-0.02 mm		+/-0.01 mm	+/-0.01 °
Maximum speed		9.5 m/sec		2 m/sec	2600 °/sec
Maximum payload		10 kg (Standard specification), 9 kg (Option specifications ^{Note 4})			
Standard cycle time: with 2kg payload ^{Note 2}		0.42 sec			
R-axis tolerable moment of inertia ^{Note 3}		0.3 kgm ²			
User wiring		0.2 sq × 20 wires			
User tubing (Outer diameter)		φ 6 × 3			
Travel limit		1.Soft limit 2.Mechanical stopper (X,Y,Z axis)			
Robot cable length		Standard: 3.5 m Option: 5 m, 10 m			
Weight		26 kg			

Note 1. This is the value at a constant ambient temperature. (X,Y axes)
 Note 2. When reciprocating 300mm in horizontal and 25mm in vertical directions and performing the coarse positioning arch operation.
 Note 3. The acceleration coefficient is set automatically in accordance with the tip weight and offset amount for R-axis moment of inertia settings.
 Note 4. Maximum payload of option specifications (with user wiring/tubing through spline type) is 9kg.

Controller

Controller	Power capacity (VA)	Operation method
RCX340	1700	Programming / I/O point trace / Remote command / Operation using RS-232C communication

Note. The movement range can be limited by changing the positions of X and Y axis mechanical stoppers. (The movement range is set to the maximum at the time of shipment.)
 See our robot manuals (installation manuals) for detailed information.
 Note. To set the standard coordinates with high accuracy, use a standard coordinate setting jig (option). Refer to the user's manual (installation manual) for more details.

Our robot manuals (installation manuals) can be downloaded from our website at the address below:
<https://global.yamaha-motor.com/business/robot/>

YK710XE-10

