

Basic specifications

	Item	Model	TS-SD
Basic specifications	Number of controllable axes		Single-axis
	Controllable robots		TRANSERVO series ^{Note}
	Current consumption		3A (Rating) 4.5A (Max.)
	Dimensions		W30 × H162 × D82mm
	Weight		Approx. 0.2kg
Basic specifications	Input power supply	Control power supply	DC24V +/-10%
		Main power supply	DC24V +/-10%
Axis control	Operating method		Pulse train control
	Control method		Closed loop vector control method
	Position detection method		Resolver
	Resolution		20480 P/rev, 4096 P/rev
	Origin search method		Incremental
External input/output	Pulse train command input		Line driver method : 500 kpps or less Open collector method : 100 kpps or less (DC5 to 24V +/-10%)
	Input		Servo ON (SERVO), reset (RESET) origin search (ORG)
	Output		Servo status (SRV-S), alarm (/ALM), positioning completion (IN-POS), return-to-origin end status (ORG-S)
	External communications		RS-232C 1CH
Options	Support software for PC		TS-Manager
General specifications	Operating temperature		0°C to 40°C
	Storage temperature		-10°C to 65°C
	Operating humidity		35% to 85%RH (non-condensing)
	Storage humidity		10% to 85%RH (non-condensing)
	Atmosphere		Indoor location not exposed to direct sunlight. No corrosive , flammable gases, oil mist, or dust particles
	Anti-vibration		All XYZ directions 10 to 57Hz unidirectional amplitude 0.075mm 57 to 150Hz 9.8m/s ²
	Protective functions		Position detection error, overheat, overload, overvoltage, low voltage, position deviation, control power voltage drop, overcurrent, motor current error, CPU error, motor line disconnection, command speed over, pulse frequency over

Note. Except for RF type sensor specifications and STH type vertical specifications.