

Accessories and part options



TS-SD

Standard accessories

● Power connector



Model KCC-M4421-00

TS-S2
TS-SH
TS-SD

● I/O cables (1m)



Model KCC-M5362-00

TS-SD

Options

● Support software TS-Manager

P.576



Model KCA-M4966-0J (Japanese)
KCA-M4966-0E (English)

TS-S2
TS-SH
TS-X
TS-P
TS-SD

● TS-Manager environment

OS	Windows 2000, XP (32bit), Vista, 7, 8 / 8.1, 10 (Supported version: V.1.4.5 or later)
CPU	Exceeding the environment recommended by the OS being used
Memory	Exceeding the environment recommended by the OS being used
Hard disk	Vacant capacity of more than 20MB in the installation destination drive
Communication port	Serial (RS-232C), USB
Applicable controllers	TS series

Note. Windows is the registered trademark of US Microsoft Corporation in U.S.A. and other countries.

● Data cables

Communication cable for TS-Manager. Select from USB cable or D-sub cable.



Model USB type (5m) KCA-M538F-A0
D-Sub type (5m) KCA-M538F-01

Note. USB driver for communication cable can also be downloaded from our website.

TS-S2
TS-SH
TS-X
TS-P
TS-SD

● Daisy chain and gateway connection cable



Model KCA-M532L-00 (300mm)

TS-S2
TS-SH
TS-X
TS-P
TS-SD

Articulated robots
YA
Linear conveyor modules
LCM100
Motor-less single axis actuator
Robonity
Compact single-axis robots
TRANSEVO
Single-axis robots
FLIP-X
Linear motor single-axis robots
PHASER
Cartesian robots
XY-X
SCARA robots
YK-X
Pick & place robots
YP-X
CLEAN
CONTROLLER
INFORMATION
Robot positioner
Pulse string driver
Robot controller
I/V2 Electric gripper
Option